

Tyfoam

South Africa Reg. No: Exempt Act/Wet No. 36 of/van 1947



Silicone based de-foaming agent for Spray Tanks. **TYFOAM** is a 10% aqueous emulsion used as a de-foaming agent in spray tanks, especially for extreme alkaline and / or acidic conditions as well as in anionic, cationic and non-ionic systems.

Sg 1.11

GROUP | ADJUVANT

DIRECTIONS FOR USE: For the best results:

- Store in a cool and dry place.
- Shake well before use.
- Add 10-20ml (not exceeding 10ppm silicone) of **TYFOAM** per 100 L water with the majority of water based agricultural remedies.
- Either apply the product into the spray tank prior to foaming or as soon as the foaming starts.
- The quality of the water may however, under extreme conditions, impact negatively on the product's efficacy.



Registration holder: **Metson Manufacturing CC.**
Co. Reg. No.: 1990/059914/23
51 Verdun Road, Kya Sands, 2196, South Africa
Tel: 011 792 8968

24 HR EMERGENCY NUMBER
0861 638 766 (Metson)

Distributed by: **Typhoon Plant Protection (Pty) Ltd.**
Co. Reg. No.: 1998/006156/07, C/O Farm Vlakfontein
Corner of the R23 Benoni Road & R550 Nigel Road
Brakpan District, Heidelberg 1438, Gauteng, South Africa
Tel: 078 737 9236

Net Mass/Volume:

1ℓ

Expiry Date:
Batch No:
Date of Manufacture:
U.N. No. Not regulated

 **Typhoon**
PLANT PROTECTION



READ LABEL IN DETAIL BEFORE OPENING THE CONTAINER. FOR FULL PARTICULARS, SEE ENCLOSED LEAFLET.
KEEP OUT OF REACH OF CHILDREN AND ANIMALS.